



# Public Signage Product Range

Q2/Q3 2012

**PHILIPS**  
sense and simplicity

# E-line Series

## Impress and captivate your audience

Deliver your marketing messages in startling clarity with the Philips E-line series. Ideal for projects which need eye-catching design at an affordable price.



## Key features

- Designed for 24/7 operation
- Low total cost of ownership
- SmartPower for energy saving
- Brightness automatically adjusts with ambient conditions
- Open Pluggable Specification slot
- RJ45 network controllability

# Technical specifications E-Line series

	BDL3245E	BDL4245E	BDL4230E	BDL4230EC	BDL4645E	BDL5545E	BDL6531E
							
<b>General</b>							
Model	32" Public Display	42" Public Display	42" Public Display	42" HaIO Public Display	46" Public Display	55" Public Display	65" Public Display
<b>Picture/Display</b>							
Diagonal Screen Size	32" (81.28cm)	42" (106.68cm)	42" (106.68cm)	42" (106.68cm)	46" (116.8cm)	55" (139.7cm)	65" (163.8cm)
Backlight Type	CCFL	CCFL	CCFL	CCFL	CCFL	CCFL	CCFL
Optimum Resolution	1920x1080p	1920x1080p	1920x1080p	1920x1080p	1920x1080p	1920x1080p	1920x1080p
Brightness	500 cd/ m <sup>2</sup>	450 cd/ m <sup>2</sup>	500 cd/ m <sup>2</sup>	500 cd/ m <sup>2</sup>	400 cd/ m <sup>2</sup>	500 cd/ m <sup>2</sup>	500 cd/ m <sup>2</sup>
Typical Contrast Ratio	1450:1	1400:1	1400:1	1400:1	4000:1	5000:1	2500:1
Response Time (Grey to Grey)	5 ms	6.5 ms	5 ms	5 ms	6.5 ms	8 ms	8 ms
Aspect Ratio	16:9	16:9	16:9	16:9	16:9	16:9	16:9
Viewing Angle (H x V)	178° x 178°	178° x 178°	178° x 178°	178° x 178°	178° x 178°	178° x 178°	178° x 178°
Pixel Pitch	0.364 x 0.364 mm	0.485 x 0.485 mm	0.485 x 0.485 mm	0.485 x 0.485 mm	0.53 x 0.53 mm	0.63 x 0.63 mm	0.63 x 0.63 mm
Display Colors	1.06 billion	16.7 million	1.06 billion	1.06 billion	1.07 billion	1.07 billion	1.07 billion
<b>Features</b>							
Video Matrix	Up to 5x5	Up to 5x5	Up to 5x5	N/A	Up to 5x5	Up to 5x5	Up to 5x5
Placement	Portrait/Landscape	Portrait/Landscape	Portrait/Landscape	Portrait/Landscape	Portrait/Landscape	Portrait/Landscape	Landscape
PBP/PIP/POP	Yes	Yes	PIP	PIP	Yes	Yes	PIP
Scheduling Functions	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Ambient Light Sensor	-	Yes	Yes	Yes	Yes	Yes	Yes
Open Pluggable Specification	-	Yes	-	-	Yes	Yes	-
Smart Insert	-	-	Yes	Yes	-	Yes	Yes
One Wire	-	-	-	-	-	-	-
<b>Energy efficiency</b>							
Energy Saving Functions	SmartPower	SmartPower	Ambient Light Sensor, SmartPower	Ambient Light Sensor, SmartPower	SmartPower	SmartPower	Ambient Light Sensor, SmartPower
Mains Power	90-264VAC 50/60 Hz	90-264VAC 50/60 Hz	90-264VAC 50/60 Hz	90-264VAC 50/60 Hz	90-264VAC 50/60 Hz	90-264VAC 50/60 Hz	90-264VAC 50/60 Hz
Consumption (On Mode)	94W	112W	120W	120W	117W	162W	358W
Consumption (SmartPower Med)	73W	91W	93W	93W	96W	132W	241W
Consumption (SmartPower High)	57W	70W	76W	76W	72W	108W	192W
Consumption (Standby)	<0.5W	<0.5W	<1W	<1W	<0.5W	<1W	<1W
Power Saving/Brightness On	50W	61W	65W	65W	63W	135W	135W
<b>Physical Specifications</b>							
Set Dimensions (W x H x D)	774 x 468 x 116 mm	992 x 584 x 116 mm	993 x 586 x 120 mm	1152mm x 745mm x 130mm	1091 x 646 x 120 mm	1299 x 769.8 x 129.9 mm	1523 x 892 x 125 mm
Dimensions with Stand	-	-	993 x 666 x 319 mm	N/A	-	1122 x 705 x 406 mm	1523x 1022 x 423 mm
Display Weight	12.8 kg	23 kg	24 kg	31.3kgs	26 kg	42 kg	53.8 kg
Bezel Width	36 mm	29 mm	29 mm	N/A	35 mm	50 mm	31 mm
Smart Insert	400 x 200 mm	400 x 200 mm	Yes	Yes	400 x 200 mm	No	Yes
VESA Mount	200 x 200 mm	200 x 200 mm	400 x 200 mm	400 x 200 mm	200 x 200 mm	400 x 200 mm	400 x 200mm
	N/A	N/A	200 x 200 mm	200 x 200 mm	N/A	200 x 200 mm	400 x 400 mm
Smart Insert Mount	N/A	N/A	100 x 100 mm	100 x 100 mm	N/A	N/A	300 x 320mm
Optional Table Stand	BM03211	BM04642	BM05411	N/A	BM04642	BM05211	BM06511
<b>Connectivity</b>							
VGA In/Out	1x/1x	1x/1x	1x/1x	1x/1x	1x/1x	1x/1x	1x/1x
HDMI In	1x	1x	1x	1x	1x	1x	1x
DVI-D In	1x	1x	1x	1x	-	-	1x
DVI-D Out	-	-	-	-	-	-	-
Display Port	-	-	-	-	-	1x	-
OPS	-	1x	-	-	1x	1x	-
LAN	1x	1x	-	-	1x	-	-
USB	-	-	-	-	-	-	-
RS232 In/Out	1x/1x	1x/1x	1x/1x	1x/1x	1x/1x	1x/1x	1x/1x
One Wire (HDMI CEC)	-	-	-	-	-	-	-
External AC	-	-	1x	1x	-	-	1x
Composite (RCA) In	1x	-	-	-	-	-	-
Composite (BNC) In/Out	1x/1x	1x/1x	1x/1x	1x/1x	1x/1x	1x	-
Composite CVBS In/Out	-	-	-	-	-	-	-
S-Video In	1x	1x	1x	1x	1x	1x	-
Component (YPbPr) In	-	-	-	-	-	1x	-
Component (BNC) In	1x	1x	-	-	1x	-	1x
Component (RCA) In	-	-	1x	1x	-	-	-
<b>Sound</b>							
Audio In/Out	2x/1x	2x/1x	2x/1x	2x/1x	1x/1x	1x/1x	1x/1x
Internal Speakers	2x 10W	2x 10W	2 x 12W	2 x 12W	2 x 10W	2 x 7W	2 x 12W
<b>Convenience</b>							
Service & Warranty	3 years	3 years	3 years	3 years	3 years	3 years	3 years
Screen Saving Functions	Pixel Shift, Low Bright	Pixel Shift, Low Bright	Pixel Shift, Low Bright	Pixel Shift, Low Bright	Pixel Shift, Low Bright	Pixel Shift, Low Bright	Pixel Shift, Low Bright
Green approvals	Energy Star 5.0, Lead Free, RoHS compliant	Energy Star 5.0, Lead Free, RoHS compliant	Energy Star 5.0, Lead Free, RoHS compliant	Lead Free, RoHS compliant	Lead Free, RoHS compliant	Energy Star 5.0, Lead Free, RoHS compliant	Lead Free, RoHS compliant

# V-Line Series

## Deliver stunning images

Broadcast your marketing messages in style with the slim bezel V-line series.

So sleek, it will make your audience stop and stare.

## Key features

- Full HD LCD display, 1920 × 1080p
- Slim bezel design for a stylish look
- Smart insert in the back cover to place a small PC
- High brightness for clearer images
- Enhanced zoom feature supports tiled matrix applications



# Technical specifications V-Line series

	BDL4251V 	BDL4651VH 	BDL4771V 	BDL5571V 	BDL6551V 
<b>General</b>					
Model	42" Slim Bezel Display	46" Sunlight Readable Display	47" Slim Bezel Display	55" Slim Bezel Display	65" Slim Bezel Display
<b>Picture/Display</b>					
Diagonal Screen Size	42" (106.68 cm)	46" (116.8 cm)	47" (119.4 cm)	55" (139.7 cm)	65" (165.1 cm)
Backlight Type	CCFL	CCFL	CCFL	CCFL	CCFL
Optimum Resolution	1920x1080p	1920x1080p	1920x1080p	1920x1080p	1920x1080p
Brightness	700 cd/ m <sup>2</sup>	1500 cd/ m <sup>2</sup>	700 cd/ m <sup>2</sup>	700 cd/ m <sup>2</sup>	700 cd/ m <sup>2</sup>
Typical Contrast Ratio	1100:1	4000:1	1200:1	1300:1	2500:1
Response Time (Grey to Grey)	9 ms	8.5 ms	9 ms	10 ms	8 ms
Aspect Ratio	16:9	16:9	16:9	16:9	16:9
Viewing Angle (H x V)	178° x 178°	178° x 178°	178° x 178°	178° x 178°	178° x 178°
Pixel Pitch	0.485 x 0.485 mm	0.53 x 0.53 mm	0.54 x 0.54 mm	0.63 x 0.63 mm	0.74 x 0.74 mm
Display Colors	1.07 billion	1.67 million	1.07 billion	1.67 million	1.07 billion
<b>Features</b>					
Video Matrix	Up to 5x5	Up to 5x5	Up to 5x5	Up to 5x5	Up to 5x5
Placement	Portrait/Landscape	Portrait/Landscape	Portrait/Landscape	Portrait/Landscape	Portrait/Landscape
PBP/PIP/POP	Yes	PIP	Yes	Yes	PIP
Scheduling Functions	Yes	Yes	Yes	Yes	Yes
Ambient Light Sensor	Yes	Yes	Yes	Yes	Yes
Open Pluggable Specification	-	-	-	-	-
Smart Insert	Yes	Yes	Yes	Yes	Yes
One Wire	-	-	Yes	Yes	-
<b>Energy efficiency</b>					
Energy Saving Functions	Ambient Light Sensor, SmartPower	Ambient Light Sensor, SmartPower	Ambient Light Sensor, SmartPower	Ambient Light Sensor, SmartPower	Ambient Light Sensor, SmartPower
Mains Power	90-264VAC 50/60 Hz	90-264VAC 50/60 Hz	90-264VAC 50/60 Hz	90-264VAC 50/60 Hz	90-264VAC 50/60 Hz
Consumption (On Mode)	133W	213W	155W	214W	314W
Consumption (SmartPower Med)	109W	165W	-	135W	246W
Consumption (SmartPower High)	89W	134W	-	110W	205W
Consumption (Standby)	<1W	<1W	<1W	<1W	<1W
Power Saving/Brightness On	74W	81W	-	115W	173W
<b>Physical Specifications</b>					
Set Dimensions (W x H x D)	968 x 559 x 123 mm	1060 x 617 x 124 mm	1080 x 625.2 x 127 mm	1252 x 723 x 122 mm	1500 x 876 x 123 mm
Dimensions with Stand	968 x 606 x 405 mm			1252 x 768 x 406 mm	1500 x 1022 x 423 mm
Display Weight	22 kg	33 kg	29 kg	26.4kg	56 kg
Bezel Width	17 mm	20 mm	20 mm	19.5 mm	31 mm
VESA Mount	400 x 200 mm	400 x 200 mm	400 x 200 mm	400 x 400 mm	400 x 400 mm
Smart Insert Mount	200 x 200 mm		200 x 200 mm		
Optional Table Stand	100 x 100 mm	100 x 100 mm	100 x 100 mm	100 x 100 mm	100 x 100 mm
	BM05211	BM05211 and BM00001		BM05211	BM05511
<b>Connectivity</b>					
VGA In/Out	1x/1x	1x/1x	1x/1x	1x/1x	1x/1x
HDMI In	1x	1x	1x	1x	1x
DVI-D In	1x	1x	1x	1x	1x
DVI-D Out	-	-	1x	Optional - CRA 71	-
Display Port	-	-	1x	-	-
OPS	-	-	-	-	-
LAN	-	-	1x	1x	-
USB	-	-	1x	1x	-
RS232 In/Out	1x/1x	1x/1x	1x/1x	1x/1x	1x/1x
OneWire (HDMI CEC)	-	-	Yes	Yes	-
External AC	1x	1x	1x	1x	1x
Composite (RCA) In	1x	-	-	1x	1x
Composite (BNC) In/Out	1x/1x	-	-	-	1x/1x
Composite CVBS In/Out	-	-	-	-	-
S-Video In	1x	-	1x	1x	1x
Component (YPbPr) In	1x	-	1x	1x	1x
Component (BNC) In	-	-	1x	-	-
Component (RCA) In	-	1x	-	-	-
<b>Sound</b>					
Audio In/Out	2x/1x	1x/1x	1x/1x	2x/1x	2x/1x
Internal Speakers	2 x 5W	2 x 12W	2 x 10W	2 x 10W	2 x 12W
<b>Convenience</b>					
Service & Warranty	3 years	3 years	3 years	3 years	3 years
Screen Saving Functions	Pixel Shift, Low Bright	Pixel Shift, Low Bright	Pixel Shift, Low Bright	Pixel Shift, Low Bright	Pixel Shift, Low Bright
Green approvals	Energy Star 5.0, Lead Free, RoHS compliant	Energy Star 5.0, Lead Free, RoHS compliant	Energy Star 5.0, Lead Free, RoHS compliant	Energy Star 5.0, Lead Free, RoHS compliant	Lead Free, RoHS compliant

# LED-series

Enthral your audience with the thin bezel, full HD LED displays

Deliver startlingly clear images in a more eco-friendly way with the edge LED displays. High on performance and reliability, yet low on power consumption, it is ideal for projects where no compromise is accepted.



## Key features

- Edge LED Backlight
- SmartPower for energy saving
- Brightness automatically adjusts with ambient conditions
- Temperature sensor measures the health condition
- Advanced anti-image sticking function

## Technical specifications LED series

	BDL5530EL	BDL4785SL
		
<b>General</b>		
Model	55" Thin Bezel Display	47" Ultra-thin Bezel Display
<b>Picture/Display</b>		
Diagonal Screen Size	55" (139.7cm)	47" (116.8 cm)
Backlight Type	Edge LED	Edge LED
Optimum Resolution	1920x1080p	1920x1080p
Brightness	400 cd/ m <sup>2</sup>	450 cd/ m <sup>2</sup>
Typical Contrast Ratio	4000:1	1300:1
Response Time (Grey to Grey)	6.5 ms	12 ms
Aspect Ratio	16:9	16:9
Viewing Angle (H x V)	178° x 178°	178° x 178°
Pixel Pitch	0.21 x 0.63 mm	0.54 x 0.54 mm
Display Colors	1.07 billion	1.06 billion
<b>Features</b>		
Video Matrix	Up to 5x5	Up to 5x5
Placement	Portrait/Landscape	Portrait/Landscape
PBP/PIP/POP	Yes	Yes
Scheduling Functions	Yes	Yes
Ambient Light Sensor	-	-
Open Pluggable Specification	Yes	N/A
Smart Insert	-	Yes
One Wire	-	Yes
<b>Energy efficiency</b>		
Energy Saving Functions	Ambient Light Sensor, SmartPower	Ambient Light Sensor, SmartPower
Mains Power	90-264VAC 50/60 Hz	90-264VAC 50/60 Hz
Consumption (On Mode)	123W	104W
Consumption (SmartPower Med)	96W	81W
Consumption (SmartPower High)	77W	51W
Consumption (Standby)	<1W	<1W
Power Saving/Brightness On	46W	56W
<b>Physical Specifications</b>		
Set Dimensions (W x H x D)	1260 x 732 x 59 mm	1085 x 632 x 38 mm
Display Weight	27.2 kg	18.8 kg
Bezel Width	25 mm	20 mm
VESA Mount	200 x 400 mm	400 x 200 mm
Smart Insert Mount	100 x 100 mm	100 x 100 mm
Optional Table Stand	BM05211 and BM00001	N/A
<b>Connectivity</b>		
VGA In/Out	1x/1x	1x/1x
HDMI In	1x	1x
DVI-D In	1x	1x
DVI-D Out	-	1x
Display Port	-	1x
OPS	-	-
LAN	-	1x
USB	-	1x
RS232 In/Out	1x/1x	1x/1x
One Wire (HDMI CEC)	-	Yes
External AC	1x	1x
Composite (RCA) In	-	-
Composite (BNC) In/Out	-	-
Composite CVBS In/Out	-	-
S-Video In	1x	-
Component (YPbPr) In	-	-
Component (BNC) In	-	1x
Component (RCA) In	1x	-
<b>Sound</b>		
Audio In/Out	1x/1x	1x/1x
Internal Speakers	2 x 12W	Optional
<b>Convenience</b>		
Service & Warranty	3 years	3 years
Screen Saving Functions	Pixel Shift, Low Bright	Pixel Shift, Low Bright
Green approvals	Energy Star 5.0, Lead Free, RoHS compliant	Energy Star 5.0, Lead Free, RoHS compliant

# Videowall-series

Create Videowalls to make your audience stop and stare

Deliver your message with a stylish seamless videowall. Whether it's used in a 2x2, 3x3 or in a 4x3 setup, your audience will be astonished! Stunning has never been this easy.



## Key features

- Zoom function for tiled matrix
- Advanced in factory colour calibration
- SmartPower for energy saving
- Edge Finishing & Alignment Installation
- Remote Control Extender

## Technical specifications Videowall series

	BDL4675XU	BDL4681XU	BDL5585XL
<b>General</b>			
Model	46" Ultra Slim Bezel Display	46" Ultra Slim Bezel Display	55" Direct-LED Ultra Slim Bezel Display
<b>Picture/Display</b>			
Diagonal Screen Size	46" (116.8 cm)	46" (116.8 cm)	55" (139.7 cm)
Backlight Type	CCFL	CCFL	Direct LED
Optimum Resolution	1366x768p	1366x768p	1920x1080p
Brightness	450 cd/ m <sup>2</sup>	700 cd/ m <sup>2</sup>	700 cd/ m <sup>2</sup>
Typical Contrast Ratio	3000:1	3000:1	3000:1
Response Time (Grey to Grey)	8 ms	8 ms	8 ms
Aspect Ratio	16:9	16:9	16:9
Viewing Angle (H x V)	178° x 178°	178° x 178°	178° x 178°
Pixel Pitch	0.746 x 0.746 mm	0.746 x 0.746 mm	0.63 x 0.63 mm
Display Colors	16.7 million	16.7 million	1.07 billion
<b>Features</b>			
Video Matrix	Up to 15x10	Up to 15x10	Up to 15x10
Placement	Portrait/Landscape	Portrait/Landscape	Portrait/Landscape
PBP/PIP/POP	PIP	PIP	Yes
Scheduling Functions	Yes	Yes	Yes
Ambient Light Sensor	-	-	-
Open Pluggable Specification	Yes	Yes	Yes
Smart Insert	-	-	Yes
OneWire	-	-	Yes
<b>Energy efficiency</b>			
Energy Saving Functions	SmartPower	SmartPower	SmartPower
Mains Power	90-264VAC 50/60 Hz	90-264VAC 50/60 Hz	90-264VAC 50/60 Hz
Consumption (On Mode)	165W	212W	150W
Consumption (SmartPower Med)	133W	172W	110W
Consumption (SmartPower High)	109W	142W	90W
Consumption (Standby)	<1W	<1W	<1W
Power Saving/Brightness On	88W	115W	84W
<b>Physical Specifications</b>			
Set Dimensions (W x H x D)	1026 x 579 x 133 mm	1026 x 579 x 133 mm	1251 x 686 x 126 mm
Dimensions with Stand	N/A	N/A	N/A
Display Weight	27.5 kg	29 kg	34 kg
Bezel Width	7.3 mm A to A	7.3 mm A to A	5.7 mm A to A
VESA Mount	400 x 200 mm	400 x 200 mm	400 x 200 mm
Smart Insert Mount	100 x 100 mm	100 x 100 mm	100 x 100 mm
Table Stand	N/A	N/A	N/A
<b>Connectivity</b>			
VGA In/Out	1x/1x	1x/1x	1x/1x
HDMI In	1x	1x	1x
DVI-D In	1x	1x	1x
DVI-D Out	-	-	1x
Display Port	-	-	1x
OPS	-	-	-
LAN	-	-	1x
USB	-	-	1x
RS232 In/Out	1x/1x	1x/1x	1x/1x
OneWire (HDMI CEC)	-	-	Yes
External AC	1x	1x	1x
Composite (RCA) In	1x	1x	-
Composite (BNC) In/Out	1x/1x	1x/1x	-
Composite CVBS In/Out	-	-	-
S-Video In	1x	1x	-
Component (YPbPr) In	-	-	-
Component (BNC) In	1x	1x	1x
Component (RCA) In	-	-	-
<b>Sound</b>			
Audio In/Out	2x/1x	2x/1x	1x/1x
Internal Speakers	2 x 12W	2 x 12W	2 x 10W
<b>Convenience</b>			
Service & Warranty	3 years	3 years	3 years
Screen Saving Functions	Pixel Shift, Low Bright	Pixel Shift, Low Bright	Pixel Shift, Low Bright
Green approvals	Energy Star 5.0, Lead Free, RoHS compliant	Energy Star 5.0, Lead Free, RoHS compliant	Energy Star 5.0, Lead Free, RoHS compliant

# 3D Display series

## 3D Stopping Power

Add an extra dimension to your professional application with Philips 3D no-glasses monitors. Based on unique technology, its stunning 3D effect immediately grabs the attention and gives a more entertaining experience to the viewer..



## Key features

- Autostereoscopic lenticular technology
- No need for special 3D glasses
- Multiple users experience 3D at the same time
- Full brightness, full contrast, true color representation
- 3D data interface

## Technical specifications 3D Display series

	BDL2331VS	BDL4251VS	BDL5571VS
<b>General</b>			
Model	23" 3D Autostereoscopic Display	42" 3D Autostereoscopic Display	55" 3D Autostereoscopic Display
<b>Picture/Display</b>			
Diagonal Screen Size	23" (58.4 cm)	42" (106.68 cm)	55" (139.7 cm)
Backlight Type	LED	CCFL	CCFL
Optimum Resolution	1920x1080p	1920x1080p	1920x1080p
Brightness	300 cd/m <sup>2</sup>	700 cd/m <sup>2</sup>	700 cd/m <sup>2</sup>
Typical Contrast Ratio	1000:1	1100:1	1300:1
Response Time (Grey to Grey)	5 ms	9 ms	10 ms
Aspect Ratio	16:9	16:9	16:9
Viewing Angle (H x V)	150° x 150°	150° x 150°	150° x 150°
Pixel Pitch	0.265 x 0.265 mm	0.485 x 0.485 mm	0.63 x 0.63 mm
Display Colors	16.7 million	1.06 billion	1.06 billion
<b>Features</b>			
Video Matrix	n/a	n/a	n/a
Placement	Landscape	Landscape	Landscape
PBP/PIP/POP	-	Yes	Yes
Scheduling Functions	-	Yes	Yes
Ambient Light Sensor	-	-	-
Open Pluggable Specification	-	Yes	Yes
Smart Insert	-	-	-
One Wire	-	-	-
<b>Energy efficiency</b>			
Energy Saving Functions	SmartPower	Ambient Light Sensor, SmartPower	Ambient Light Sensor, SmartPower
Mains Power	100-240VAC 50/60 Hz	90-264VAC 50/60 Hz	90-264VAC 50/60 Hz
Consumption (On Mode)	28.62W	165W	214W
Consumption (SmartPower Med)			
Consumption (SmartPower High)			
Consumption (Standby)	0.1W	<1W	<1W
Power Saving/Brightness On			
<b>Physical Specifications</b>			
Set Dimensions (W x H x D)	566 x 360 x 50 mm	968 x 559 x 132 mm	1252 x 723 x 133 mm
Dimensions with Stand	566 x 499 x 249 mm	968 x 606 x 405 mm	1252 x 773 x 405 mm
Display Weight	5.7 kg	35 kg	75 kg
Bezel Width		17 mm	19.5 mm
VESA Mount		400 x 200 mm	400 x 400 mm
Smart Insert Mount		200 x 200 mm	
Optional Table Stand	Included	BM05211	BM05211
<b>Connectivity</b>			
VGA In/Out	1x	1x/1x	1x/1x
HDMI In	-	1x	1x
DVI-D In	1x	1x	1x
DVI-D Out	-	-	Optional
Display Port	-	-	1x
OPS	-	-	-
LAN	-	-	1x
USB	1x	-	1x
RS232 In/Out	-	1x/1x	1x/1x
One Wire (HDMI CEC)	-	-	-
External AC	-	1x	1x
Composite (RCA) In	-	1x	1x
Composite (BNC) In/Out	-	1x/1x	-
Composite CVBS In/Out	-	-	-
S-Video In	-	1x	1x
Component (YPbPr) In	-	1x	1x
Component (BNC) In	-	-	-
Component (RCA) In	-	-	-
<b>Sound</b>			
Audio In/Out	1x	2x/1x	2x/1x
Internal Speakers	2 x 1.5W	2 x 5W	2 x 10W
<b>Convenience</b>			
Service & Warranty	1 year	1 year	1 year
Screen Saving Functions	Pixel Shift, Low Bright	Pixel Shift, Low Bright	Pixel Shift, Low Bright
Green approvals	Energy Star 5.0, Lead Free, RoHS compliant	Energy Star 5.0, Lead Free, RoHS compliant	Energy Star 5.0, Lead Free, RoHS compliant

# Multi-touch Series

Open up a new era of interaction

Take audience participation to a whole new level with latest multi-user touch technologies. With your own touch applications, the sky's the limit!












## Key features

- Optical or Infra-Red Multi-touch technology
- Choice between 2, 4, 6 or 32 simultaneous touchpoints
- Smart insert in the back cover to place a small PC
- SmartPower for energy saving
- Brightness automatically adjusts with ambient conditions

## Technical specifications Multi-touch Series

	BDL4230ET	BDL5545ET	BDL6545AT	BDT3215EM
<b>General</b>				
Model	42" Multi Touch Screen	55" Multi Touch Display	65" Multi Touch Display	32" Multi User Touch Display
<b>Picture/Display</b>				
Diagonal Screen Size	42" (106.68cm)	55" (139.7cm)	65" (165.1 cm)	32" (81.28cm)
Touchscreen Type	Optical Imaging	Optical Imaging	Optical Imaging	Infrared
Touch points	2	2	2	6
Backlight Type	CCFL	CCFL	CCFL	CCFL
Optimum Resolution	1920x1080p	1920x1080p	1920x1080p	1360 x 768p
Brightness	500 cd/ m <sup>2</sup>	500 cd/ m <sup>2</sup>	500 cd/ m <sup>2</sup>	450 cd/ m <sup>2</sup>
Typical Contrast Ratio	1400:1	5000:1	5000:1	3500:1
Response Time (Grey to Grey)	5 ms	8 ms	8 ms	8 ms
Aspect Ratio	16:9	16:9	16:9	16:9
Viewing Angle (H x V)	178° x 178°	178° x 178°	178° x 178°	178° x 178°
Pixel Pitch	0.485 x 0.485 mm	0.63 x 0.63 mm	0.744 x 0.744 mm	0.511 x 0.511 mm
Display Colors	1.06 billion	1.07 billion	1.07 billion	16.7 million
<b>Features</b>				
Video Matrix	n/a	n/a	n/a	n/a
Placement	Portrait/Landscape	Portrait/Landscape	Landscape	Portrait/Landscape/Horizontal
PBP/PIP/POP	Yes	Yes	Yes	-
Scheduling Functions	Yes	Yes	Yes	Yes
Open Pluggable Specification	-	Yes	Yes	-
Smart Insert	Yes	Yes	Yes	n/a
OneWire	-	-	-	-
<b>Energy efficiency</b>				
Energy Saving Functions	Ambient Light Sensor, SmartPower	Ambient Light Sensor, SmartPower	Ambient Light Sensor, SmartPower	SmartPower
Mains Power	90-264VAC 50/60 Hz	90-264VAC 50/60 Hz	90-264VAC 50/60 Hz	90-264VAC 50/60 Hz
Consumption (On Mode)				
Consumption (SmartPower Med)	116W			54W
Consumption (SmartPower High)	96W			44W
Consumption (Standby)	<1W	<1W	<1W	<1W
Power Saving/Brightness On	76W			38W
<b>Physical Specifications</b>				
Set Dimensions (W x H x D)	993 x 586 x 128 mm	1299 x 769.8 x 143.7 mm	1523.6 x 889.2 x 138.8 mm	810 x 544 x 122 mm
Dimensions with Stand	993 x 666 x 319 mm	-	-	-
Display Weight				
Bezel Width	30 mm	41.4 mm	45 l/r, 42 t, 39 b mm	65,26 mm horizontal, 61,26 mm vertical
VESA Mount	400 x 200 mm	400 x 200 mm 200 x 200 mm	400 x 200 mm 200 x 200 mm	400 x 200 mm 200 x 100 mm
Smart Insert Mount	100 x 100 mm	100 x 100 mm	100 x 100 mm	n/a
Optional Table Stand	BM0521 I and BM0000 I	BM0521 I	BM0651 I	incl. horizontal table stand
<b>Connectivity</b>				
VGA In/Out	1x/1x	1x/1x	1x/1x	1x/1x
HDMI In	1x	1x	1x	1x
DVI-D In	1x	1x	1x	-
DVI-D Out	-	-	-	-
Display Port	-	1x	-	-
OPS	-	1x	1x	-
LAN	-	-	-	-
USB	-	-	-	1 to connect touch to PC
RS232 In/Out	1x/1x	1x/1x	1x/1x	1x/1x
OneWire (HDMI CEC)	-	-	-	-
AC Out				
Composite (RCA) In	-	-	-	1x
Composite (BNC) In/Out	1x/1x	-	1x	1x/1x
Composite CVBS In/Out				
S-Video In	1x	-	1x	1x
Component (YPbPr) In	-	-	-	-
Component (BNC) In	-	1x	-	1x
Component (RCA) In	1x	-	1x	-
<b>Sound</b>				
Audio In/Out	2x/1x	2x/1x	2x/1x	2x/1x
Internal Speakers	2 x 12W	2 x 7W	2 x 12W	2 x 7W
<b>Convenience</b>				
Service & Warranty	3 years	3 years	3 years	2 years
Screen Saving Functions	Pixel Shift, Low Bright	Pixel Shift, Low Bright	Pixel Shift, Low Bright	Pixel Shift, Low Bright
Green approvals	Energy Star 5.0, Lead Free, RoHS compliant	Energy Star 5.0, Lead Free, RoHS compliant	Lead Free, RoHS compliant	Lead Free, RoHS compliant
Software compatible	Win 7, Omnitapps, MAC Lion OS	Win 7, Omnitapps, MAC Lion OS	Win 7, Omnitapps, MAC Lion OS	Win 7, Omnitapps, MAC Lion OS

# Technical specifications Multi-touch Series

	BDT4225EM	BDT4251VM	BDT5530EM	BDT551VM	BDT6531EM	BDT6551VM	BDT4225ET	BDT5530ET	BDT3215EK	BDT4225EK	BDT5530EK
General											
Model	42" Multi User Touch Display	42" Multi User Touch Display	55" Multi User Touch Display	55" Multi User Touch Display	65" Multi User Touch Display	65" Multi User Touch Display	42" Multi User Touch Table	55" Multi User Touch Table	Information Kiosk 32" landscape 45 °	Information Kiosk 42" landscape 45 °	Information Kiosk 55" landscape 45 °
Picture/Display											
Diagonal Screen Size	42" (106.68cm)	42" (106.68 cm)	55" (138.6 cm)	55" (139.7 cm)	65" (165.1cm)	65" (165.1 cm)	42" (106.68cm)	55" (138.6 cm)	32" (81.28cm)	42" (106.68 cm)	55" (139.7cm)
Infrared Type	Infrared	Infrared	Infrared	Infrared	Infrared	Infrared	Infrared	Infrared	Infrared	Infrared	Infrared
Touch points	6 or 32	6	6 or 32	6	6	6	6 or 32	6 or 32	6	6 or 32	6 or 32
Backlight Type	CCFL	CCFL	Edge LED	CCFL	CCFL	CCFL	CCFL	Edge LED	CCFL	CCFL	Edge LED
Optimum Resolution	1920x1080p	1920x1080p	1920x1080p	1920x1080p	1920x1080p	1920x1080p	1920x1080p	1920x1080p	1366 x 768p	1920x1080p	1920x1080p
Brightness	500 cd/ m <sup>2</sup>	700 cd/ m <sup>2</sup>	400 cd/ m <sup>2</sup>	700 cd/ m <sup>2</sup>	500 cd/ m <sup>2</sup>	700 cd/ m <sup>2</sup>	500 cd/ m <sup>2</sup>	450 cd/ m <sup>2</sup>	450 cd/ m <sup>2</sup>	700 cd/ m <sup>2</sup>	400 cd/ m <sup>2</sup>
Typical Contrast Ratio	1400:1	1100:1	4000:1	4000:1	2500:1	2500:1	1400:1	4000:1	3500:1	1100:1	4000:1
Response Time (Grey to Grey)	5 ms	9 ms	6.5 ms	10 ms	8 ms	8 ms	5 ms	6.5 ms	8 ms	9 ms	6.5 ms
Aspect Ratio	16:9	16:9	16:9	16:9	16:9	16:9	16:9	16:9	16:9	16:9	16:9
Viewing Angle (H x V)	178° x 178°	178° x 178°	178° x 178°	178° x 178°	178° x 178°	178° x 178°	178° x 178°	178° x 178°	178° x 178°	178° x 178°	178° x 178°
Pixel Pitch	0.485 x 0.485 mm	0.485 x 0.485 mm	0.21 x 0.63 mm	0.63 x 0.63 mm	0.21 x 0.63 mm	0.74 x 0.74 mm	0.485 x 0.485 mm	0.21 x 0.63 mm	0.511 x 0.511 mm	0.485 x 0.485 mm	0.21 x 0.63 mm
Display Colors	1.07 billion	1.07 billion	1.07 billion	16.7 million	1.07 billion	1.07 billion	1.07 billion	1.07 billion	1.07 billion	1.07 billion	1.07 billion
Features											
Video Matrix	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
Placement	Portrait/Landscape/Horizontal	Portrait/Landscape/Horizontal	Portrait/Landscape/Horizontal	Portrait/Landscape	Landscape Only	Portrait/Landscape	Horizontal	Horizontal	landscape 45°	landscape 45°	landscape 45°
PBP/PIP/POP	-	-	-	-	-	-	-	-	-	-	-
Scheduling Functions	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Open Pluggable Specification	-	-	-	-	-	-	-	-	-	-	-
Smart Insert	n/a	Yes	n/a	Yes	Yes	Yes	n/a	n/a	n/a	n/a	n/a
One Wire	-	-	-	Yes	-	-	-	-	-	-	-
Energy efficiency											
Energy Saving Functions	SmartPower	Ambient Light Sensor, SmartPower	Ambient Light Sensor, SmartPower	Ambient Light Sensor, SmartPower	Ambient Light Sensor, SmartPower	Ambient Light Sensor, SmartPower	SmartPower	Ambient Light Sensor, SmartPower	SmartPower	SmartPower	Ambient Light Sensor, SmartPower
Mains Power	90-264VAC 50/60 Hz	90-264VAC 50/60 Hz	90-264VAC, 50/60 Hz	90-264VAC 50/60 Hz	90-264VAC 50/60 Hz	90-264VAC 50/60 Hz	90-264VAC 50/60 Hz	90-264VAC 50/60 Hz	90-264VAC 50/60 Hz	90-264VAC 50/60 Hz	90-264VAC 50/60 Hz
Consumption (On Mode)	135W	133W	123W	175W	358W	314W	135W	123W	67W	133W	123W
Consumption (SmartPower Med)	106W	109W	96W	135W	241W	246W	106W	96W	54W	109W	96W
Consumption (SmartPower High)	86W	89W	77W	110W	192W	205W	86W	77W	44W	89W	77W
Consumption (Standby)	<1W	<1W	<1W	<1W	<1W	<1W	<1W	<1W	<1W	<1W	<1W
Power Saving/Brightness On	75W	74W	46W	115W	135W	187W	75W	46W	38W	74W	46W
Physical Specifications											
Set Dimensions (W x H x D)	1024 x 617 x 140,79 mm	1008 x 598 x 134,5 mm	1350 x 815 x 74,84 mm	1252 x 723 x 122 mm	1525 x 891 x 140,5 mm	1499 x 875 x 140,7 mm	1024 x 936 x 617 mm	1350 x 869,8 x 815 mm	900 x 550 x 1345 mm	1008 x 550 x 1371	1260 x 630 x 1388 mm
Dimensions with Stand	-	-	-	-	-	-	-	-	-	-	-
Display Weight	38 kg	45 kg	37 kg	49 kg	74 kg	85 kg	72 kg	65 kg	68 kg	71 kg	92 kg
Bezel Width	46 mm horizontal, 44,5mm vertical	35,5 mm horizontal, 36,5 mm vertical	62,50 mm	36,6 mm horizontal, 36,3 mm vertical	40,50 mm horizontal, 41,60 mm vertical	32,5 mm horizontal, 28,5 mm vertical	46 mm horizontal, 44,5mm vertical	62,50 mm	-	-	-
VESA Mount	400 x 200 mm 200 x 200 mm	400 x 200 mm 200 x 200 mm	400 x 400 200 x 400	400 x 400 mm	400 x 200mm 400 x 400 mm	400 x 200 mm 400 x 400 mm	n/a	n/a	n/a	n/a	n/a
Smart Insert Mount	n/a	100 x 100 mm	n/a	100 x 100 mm	100 x 100 mm	100 x 100 mm	n/a	n/a	n/a	n/a	n/a
Table Stand	incl. horizontal table stand	n/a	incl. horizontal table stand	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
Connectivity											
VGA In/Out	1x/1x	1x/1x	1x/1x	1x/1x	1x/1x	1x/1x	1x/1x	1x/1x	1x/1x	1x/1x	1x/1x
HDMI In	1x	1x	1x	1x	1x	1x	1x	1x	1x	1x	1x
DVI-D In	1x	1x	1x	1x	1x	1x	1x	1x	-	1x	1x
DVI-D Out	-	-	-	Optional	-	-	-	-	-	-	-
Display Port	-	-	-	1x	-	-	-	-	-	-	-
OPS	-	-	-	-	-	-	-	-	-	-	-
LAN	-	-	1x	-	-	-	1x	1x	1x	1x	1x
USB	1 to connect touch to PC	1 to connect touch to PC	1 to connect touch to PC	2x 1 to connect touch to PC	1 to connect touch to PC	1 to connect touch to PC	1 to connect touch to PC	1 to connect touch to PC	1 to connect touch to PC	1 to connect touch to PC	1 to connect touch to PC
RS232 In/Out	1x/1x	1x/1x	1x/1x	1x/1x	1x/1x	1x/1x	1x/1x	1x/1x	1x/1x	1x/1x	1x/1x
One Wire (HDMI CEC)	-	-	-	-	-	-	-	-	-	-	-
AC Out	-	-	-	-	1x	1x	-	1x	-	1x	1x
Composite (RCA) In	1x	1x	-	1x	-	1x	1x	-	1x	1x	-
Composite (BNC) In/Out	1x/1x	1x/1x	-	-	-	1x/1x	1x/1x	-	1x/1x	1x/1x	-
Composite CVBS In/Out	-	-	-	-	-	-	-	-	-	-	-
S-Video In	1x	1x	1x	1x	-	1x	1x	1x	1x	1x	1x
Component (YPbPr) In	-	1x	-	1x	-	1x	-	-	-	1x	-
Component (BNC) In	1x	-	-	-	1x	-	1x	-	1x	-	-
Component (RCA) In	-	-	1x	-	-	-	-	1x	-	-	1x
Sound											
Audio In/Out	2x/1x	2x/1x	1x/1x	2x/1x	1x/2x	2x/1x	2x/1x	1x/1x	2x/1x	2x/1x	1x/1x
Internal Speakers	2 x 7W	2 x 5W	2 x 12W	2 x 10W	2 x 12W	2 x 12W	2 x 7W	2 x 12W	2 x 7W	2 x 5W	2 x 12W
Convenience											
Service & Warranty	2 years	3 years	2 years	3 years	3 years	3 years	2 years	2 years	2 years	2 years	2 years
Screen Saving Functions	Pixel Shift, Low Bright	Pixel Shift, Low Bright	Pixel Shift, Low Bright	Pixel Shift, Low Bright	Pixel Shift, Low Bright	Pixel Shift, Low Bright	Pixel Shift, Low Bright	Pixel Shift, Low Bright	Pixel Shift, Low Bright	Pixel Shift, Low Bright	Pixel Shift, Low Bright
Green approvals	Lead Free, RoHS compliant Win 7, Omnitapps, MAC Lion OS	Lead Free, RoHS compliant Win 7, Omnitapps, MAC Lion OS	Lead Free, RoHS compliant Win 7, Omnitapps, MAC Lion OS	Lead Free, RoHS compliant Win 7, Omnitapps, MAC Lion OS	Lead Free, RoHS compliant Win 7, Omnitapps, MAC Lion OS	Lead Free, RoHS compliant Win 7, Omnitapps, MAC Lion OS	Lead Free, RoHS compliant Win 7, Omnitapps, MAC Lion OS	Lead Free, RoHS compliant Win 7, Omnitapps, MAC Lion OS	Lead Free, RoHS compliant Win 7, Omnitapps, MAC Lion OS	Lead Free, RoHS compliant Win 7, Omnitapps, MAC Lion OS	Lead Free, RoHS compliant Win 7, Omnitapps, MAC Lion OS
Software compatible											

# Technical specifications Multi-touch Series

	BDT4251TX	BDT4251TI	BDT5571TX	BDT5571TI	BDT4651TO	BDT4225EX	BDT4251VX	BDT5530EX	BDT5571VX	BDT4225KX	BDT5530KX
<b>General</b>											
Model	Totem 42" portrait	Totem 42" portrait	Totem 55" portrait	Totem 55" portrait	Outdoor Totem 46" portrait	Vandal proof 42" Multi Touch Display	Vandal proof 42" Multi Touch Display	Vandal proof 55" Multi Touch Display	Vandal proof 55" Multi Touch Display	Vandal proof 42" Information Kiosk	Vandal proof 55" Information Kiosk
Picture/Display											
Diagonal Screen Size	42" (106.68 cm)	42" (106.68 cm)	55" (139.7 cm)	55" (139.7 cm)	46" (116.8 cm)	42" (106.68cm)	42" (106.68 cm)	55" (138.6 cm)	55" (139.7 cm)	42" (106.68 cm)	55" (139.7cm)
Touchscreen Type	Capacitive	Infrared	Capacitive	Infrared	Capacitive	Capacitive	Capacitive	Capacitive	Capacitive	Capacitive	Capacitive
Touch points	0 or 2	6	0 or 2	6	0 or 2	2	2	2	2	2	2
Backlight Type	CCFL	CCFL	CCFL	CCFL	CCFL	CCFL	CCFL	Edge LED	CCFL	CCFL	Edge LED
Optimum Resolution	1920x1080p	1920x1080p	1920x1080p	1920x1080p	1920x1080p	1920x1080p	1920x1080p	1920x1080p	1920x1080p	1920x1080p	1920x1080p
Brightness	700 cd/ m <sup>2</sup>	700 cd/ m <sup>2</sup>	700 cd/ m <sup>2</sup>	700 cd/ m <sup>2</sup>	1500 cd/ m <sup>2</sup>	500 cd/ m <sup>2</sup>	700 cd/ m <sup>2</sup>	400 cd/ m <sup>2</sup>	700 cd/ m <sup>2</sup>	700 cd/ m <sup>2</sup>	400 cd/ m <sup>2</sup>
Typical Contrast Ratio	1100:1	1300:1	1300:1	1300:1	4000:1	1400:1	1100:1	4000:1	1300:1	1100:1	4000:1
Response Time (Grey to Grey)	9 ms	9 ms	10 ms	10 ms	8.5 ms	5 ms	9 ms	6.5 ms	10 ms	9 ms	6.5 ms
Aspect Ratio	16:9	16:9	16:9	16:9	16:9	16:9	16:9	16:9	16:9	16:9	16:9
Viewing Angle (H x V)	178° x 178°	178° x 178°	178° x 178°	178° x 178°	178° x 178°	178° x 178°	178° x 178°	178° x 178°	178° x 178°	178° x 178°	178° x 178°
Pixel Pitch	0.485 x 0.485 mm	0.485 x 0.485 mm	0.63 x 0.63 mm	0.63 x 0.63 mm	0.53 x 0.53 mm	0.485 x 0.485 mm	0.485 x 0.485 mm	0.21 x 0.63 mm	0.63 x 0.63 mm	0.485 x 0.485 mm	0.21 x 0.63 mm
Display Colors	1.07 billion	1.07 billion	16.7 million	16.7 million	16.7 million	1.07 billion	1.07 billion	1.07 billion	1.07 billion	1.07 billion	1.07 billion
<b>Features</b>											
Video Matrix	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Placement	Portrait only	Portrait only	Portrait only	Portrait only	Portrait only	Portrait/Landscape	Portrait/Landscape	Portrait/Landscape	Portrait/Landscape	landscape 45°	landscape 45°
PBP/PIP/POP	-	-	-	-	-	-	-	-	-	-	-
Scheduling Functions	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Open Pluggable Specification	-	-	-	-	-	-	-	-	-	-	-
Smart Insert	N/A	N/A	N/A	N/A	N/A	N/A	Yes	N/A	Yes	N/A	N/A
OneWire	-	-	Yes	Yes	-	-	-	-	Yes	-	-
<b>Energy efficiency</b>											
Energy Saving Functions	SmartPower	SmartPower	SmartPower	SmartPower	SmartPower	SmartPower	Ambient Light Sensor, SmartPower	Ambient Light Sensor, SmartPower	Ambient Light Sensor, SmartPower	SmartPower	Ambient Light Sensor, SmartPower
Mains Power	90-264VAC 50/60 Hz	90-264VAC 50/60 Hz	90-264VAC 50/60 Hz	90-264VAC 50/60 Hz	90-264VAC 50/60 Hz	90-264VAC 50/60 Hz	90-264VAC 50/60 Hz	90-264VAC 50/60 Hz	90-264VAC 50/60 Hz	90-264VAC 50/60 Hz	90-264VAC 50/60 Hz
Consumption (On Mode)	133W			175W		135W	133W	123W	175W	133W	123W
Consumption (SmartPower Med)	109W	109W	135W	135W	-	106W	109W	96W	135W	109W	96W
Consumption (SmartPower High)	89W	89W	110W	110W	-	86W	89W	77W	110W	89W	77W
Consumption (Standby)	<1W	<1W	<1W	<1W	-	<1W	<1W	<1W	<1W	<1W	<1W
Power Saving/Brightness On	74W	74W	115W	115W	-	75W	74W	46W	115W	74W	46W
<b>Physical Specifications</b>											
Set Dimensions (W x H x D)	598 x 2011 x 185 mm	598 x 2011 x 185 mm	759 x 2152 x 185 mm	759 x 2152 x 185 mm	2250 x 996 x 299 mm	1024 x 617 x 140,79 mm	1008 x 598 x 134,5 mm	1350 x 815 x 74,84 mm	1252 x 723 x 122 mm	1008 x 550 x 1371	1260 x 630 x 1388 mm
Dimensions with Stand	-	-	-	-	-	-	-	-	-	-	-
Display Weight	120 kg	120 kg	145 kg	145 kg	300 kg	38 kg	45 kg	37 kg	49 kg	71 kg	92 kg
Bezel Width	-	-	-	-	-	46 mm horizontal, 44,5mm vertical	35,5 mm horizontal, 36,5 mm vertical	62,50 mm	36,6 mm horizontal, 36,3 mm vertical	46 mm horizontal, 44,5mm vertical	62,50 mm
VESA Mount	N/A	N/A	N/A	N/A	N/A	400 x 200 mm 200 x 200 mm	400 x 200 mm 200 x 200 mm	400 x 400 200 x 400	400 x 400 mm	N/A	N/A
Smart Insert Mount	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	100 x 100 mm	N/A	N/A
Table Stand	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
<b>Connectivity</b>											
VGA In/Out	1x/1x	1x/1x	1x/1x	1x/1x	1x/1x	1x/1x	1x/1x	1x/1x	1x/1x	1x/1x	1x/1x
HDMI In	1x	1x	1x	1x	1x	1x	1x	1x	1x	1x	1x
DVI-D In	1x	1x	1x	1x	1x	1x	1x	1x	1x	1x	1x
DVI-D Out	-	-	Optional	Optional	-	-	-	-	Optional	-	-
Display Port	-	-	1x	1x	-	-	-	-	1x	-	-
OPS	-	-	-	-	-	-	-	-	-	-	-
LAN	1x	1x	1x	1x	1x	1x	1x	1x	1x	1x	1x
USB	1 to connect touch to PC	1 to connect touch to PC	1 to connect touch to PC	1 to connect touch to PC	1 to connect touch to PC	1 to connect touch to PC	1 to connect touch to PC	1 to connect touch to PC	2x 1 to connect touch to PC	1 to connect touch to PC	1 to connect touch to PC
RS232 In/Out	1x/1x	1x/1x	1x/1x	1x/1x	1x/1x	1x/1x	1x/1x	1x/1x	1x/1x	1x/1x	1x/1x
OneWire (HDMI CEC)	-	-	-	-	-	-	-	-	-	-	-
AC Out	1x	1x	1x	1x	1x	-	1x	1x	1x	1x	1x
Composite (RCA) In	1x	1x	1x	1x	1x	1x	1x	1x	1x	1x	1x
Composite (BNC) In/Out	1x/1x	1x/1x	-	-	-	1x/1x	1x/1x	-	-	1x/1x	-
Composite CVBS In/Out	-	-	-	-	-	-	-	-	-	-	-
S-Video In	1x	1x	1x	1x	-	1x	1x	1x	1x	1x	1x
Component (YPbPr) In	1x	1x	1x	1x	-	-	1x	-	1x	1x	-
Component (BNC) In	-	-	-	-	-	1x	-	-	-	-	-
Component (RCA) In	-	-	-	-	1x	-	-	1x	-	-	1x
<b>Sound</b>											
Audio In/Out	2x/1x	2x/1x	2x/1x	2x/1x	1x/1x	2x/1x	2x/1x	1x/1x	2x/1x	2x/1x	1x/1x
Internal Speakers	2 x 5W	2 x 5W	2 x 10W	2 x 10W	2 x 12W	2 x 7W	2 x 5W	2 x 12W	2 x 10W	2 x 5W	2 x 12W
<b>Convenience</b>											
Service & Warranty	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years
Screen Saving Functions	Pixel Shift, Low Bright	Pixel Shift, Low Bright	Pixel Shift, Low Bright	Pixel Shift, Low Bright	Pixel Shift, Low Bright	Pixel Shift, Low Bright	Pixel Shift, Low Bright	Pixel Shift, Low Bright	Pixel Shift, Low Bright	Pixel Shift, Low Bright	Pixel Shift, Low Bright
Green approvals	Lead Free, RoHS compliant	Lead Free, RoHS compliant	Lead Free, RoHS compliant	Lead Free, RoHS compliant	Lead Free, RoHS compliant	Lead Free, RoHS compliant	Lead Free, RoHS compliant	Lead Free, RoHS compliant	Lead Free, RoHS compliant	Lead Free, RoHS compliant	Lead Free, RoHS compliant
Software compatible	Win 7, Omnitapps	Win 7, Omnitapps, MAC Lion OS	Win 7, Omnitapps	Win 7, Omnitapps, MAC Lion OS	N/A	Win 7, Omnitapps	Win 7, Omnitapps	Win 7, Omnitapps	Win 7, Omnitapps	Win 7, Omnitapps	Win 7, Omnitapps



More info: [www.philips.com/publicsignagesolutions](http://www.philips.com/publicsignagesolutions)

© 2012 Koninklijke Philips Electronics N.V.  
All rights reserved. Reproduction in whole or in parts is Not prohibited  
without the prior written consent of the copyright owner.

Executive production Norvell Jefferson, The Netherlands